

NANO EXPRESS

Open Access

TiO₂-coated nanostructures for dye photo-degradation in water

Viviana Scuderi¹, Giuliana Impellizzeri^{1*}, Lucia Romano^{1,2}, Mario Scuderi³, Giuseppe Nicotra³, Kristin Bergum⁴, Alessia Irrera⁵, Bengt G Svensson⁴ and Vittorio Privitera¹

Abstract

The photocatalytic efficiency of a thin-film TiO₂-coated nanostructured template is studied by dye degradation in water. The nanostructured template was synthesized by metal-assisted wet etching of Si and used as substrate for the deposition of a thin film of TiO₂ (10 nm thick) by atomic layer deposition. A complete structural characterization was made by scanning and transmission electron microscopies. The significant photocatalytic performance was evaluated by the degradation of two dyes in water: methylene blue and methyl orange. The relevance of the reported results is discussed, opening the route toward the application of the synthesized nanostructured TiO₂ for water purification.

Keywords: TiO₂; Nanostructure; Photocatalysis; Water

PACS: 81.07.-b; 81.15.Gh; 89.60.Ec

Background

Water purification has become a worldwide problem, in particular in industrialized countries, where wastewaters usually contain organic pollutants, such as dyes from the textile industry, leather tanning industry, paper production, food technology, agricultural research, pharmaceutical industry, etc. [1]. Due to their large-scale production and extensive applications, the organic dyes have become an important part of industrial wastewaters. Indeed, of the 7×10^5 tons, more than 10% to 15% is lost in the wastewaters during the manufacturing and application processes [2]. The discharge of these colored compounds in the environment raises much concern because of the toxic effects on the ecological systems. Among others, two families of dyes - azo dyes and thiazine dyes - can cause serious health risk factors (see, for examples, refs. [3] and [4], respectively). It is also well known that some azo dyes are highly carcinogenic [5]. Since conventional wastewater treatment plants cannot degrade the majority of these pollutants, powerful methods for the decontamination of dyes in wastewaters have received increasing attention over the past decade.

Semiconductor photocatalysts have shown a great potential in water purification [6-8]. Among them, TiO₂ (commonly called 'titania') is one of the most studied due to its unique characteristics: non-toxicity, good chemical stability, strong mechanical properties, low cost, and excellent photocatalytic performance [9]. The mechanism behind TiO₂ photocatalysis has been deeply investigated: (1) electron-hole pairs are photo-generated upon bandgap excitation (3.15 eV for the anatase phase, 3.05 eV for the rutile crystalline phase [10]); (2) depending on the excitation lifetime relative to that of charge recombination, a net fraction of photo-generated charges can reach the surface; (3) the photo-generated charges can react with water by producing radical species, such as OH⁻, which are directly involved in the oxidation processes of water pollutants. TiO₂ nanostructures can offer advantages such as high surface-area-to-volume ratio, enhancing in this way the amount of the photo-generated charges. TiO₂ nanoparticles have been largely tested and demonstrated successful results [11]. However, there are some issues that strongly limit their application: poor light penetration due to nanoparticle agglomeration and the post-recovery of the particles after the water treatment [8]. An alternative to suspension is the thin film system where the photocatalyst is present as a thin film on the reactor walls [12], and recent investigations are oriented toward photocatalyst

* Correspondence: giuliana.impellizzeri@ct.infn.it

¹CNR-IMM MATIS, Via S. Sofia 64, Catania 95123, Italy

Full list of author information is available at the end of the article

immobilization [7,8]. This kind of reactor promotes light penetration, and the coated area may be increased by packing with a material coated with the photocatalyst. A recent work experimentally quantified the charge diffusion length in high-quality titania: 3.2 nm for the anatase phase and 1.6 nm for the rutile phase, showing that a surface region of a few-nanometer depth provides charge carriers for photoreactions [13]. This clearly means that the use of a thick titania is useless.

Based on the above-mentioned considerations, we studied the photocatalytic activity of a TiO₂ thin film covering a nanostructured Si template in degrading dyes in water. The titania film (10 nm thick) was obtained by atomic layer deposition (ALD). The ALD technique provided the possibility to efficiently enhance the exposed surface of the TiO₂ since it offers an excellent conformality on high-aspect-ratio structures, as well as a great thickness control at atomic level [14]. The ALD was already used to create thicker (>30 nm) nanostructured TiO₂, starting from nanotemplates [15,16]. Of course, thinner layers avoid a waste of material and enhance the nanostructuring effect. It is worth noting that highly anisotropic nanostructures such as nanotubes, nanorods, nanowires, and nanoribbons have been explored, but it is hard to compare the data from the literature in order to disentangle the real effect of the surface/volume enhancement from other contributions because of the complexity of the photocatalysis mechanism and the delicacy of the characterization techniques [12]. For example, most nanostructures are polycrystalline and the effect of grain boundaries and structural defects on charge transport cannot be neglected, especially when highlighting the beneficial effect of a certain photocatalyst shape over another one. Therefore, it is relevant to test the photocatalytic properties on a nanostructured material that has a reference with the same structural and compositional properties in a flat shape. In our experiment, the ALD provided a perfect tool to produce a reference flat sample with the same characteristics of the nanostructured sample.

Methods

Nanostructured Si templates were obtained starting from p-type (10^{16} B/cm³), (100) Si wafers. The samples were UV oxidized and dipped in a 5% HF solution so as to obtain a clean and oxide-free Si surface. Then a thin Au layer (2 nm) was deposited on Si at room temperature by electron beam evaporation by using high-purity (99.9%) gold pellets as source. Finally, the samples were etched at room temperature in a solution of HF (5 M) and H₂O₂ (0.44 M) [17]. The templates were covered with a thin layer of TiO₂ (10 nm thick), deposited by ALD, using a Beneq TFS 200 system (Beneq Oy, Espoo, Finland), with TiCl₄ (99.9%) and de-ionized water as precursors, at a deposition temperature of 200°C. Nitrogen (>99.999%) was

used as carrier gas. This sample typology will be hereafter called ‘TiO₂/Si-template’. TiO₂ flat films (10 nm thick) deposited on flat Si substrates were used as a reference, hereafter simply called ‘TiO₂’.



The structural characterization was performed by scanning electron microscopy (SEM) with a field emission Zeiss Supra 25 (Carl Zeiss, Inc., Oberkochen, Germany) and by transmission electron microscopy (TEM) with a JEOL JEM-2010 F (JEOL Ltd., Akishima-shi, Japan) operated at 200 keV and equipped with a post-column Gatan GIF 2001 energy image filter (Gatan, Inc., Pleasanton, CA, USA).

The photocatalytic activity of the investigated materials was tested by the degradation of two dyes: methylene blue (MB) and methyl orange (MO), complying with the ISO protocol [18]. The employed MB was a 0.05-wt% solution in water (code number: 319112, by Sigma-Aldrich Corporation, St. Louis, MO, USA), while the MO was a 0.1% solution (code number: 34576, by Sigma-Aldrich Corporation, St. Louis, MO, USA). The irradiation was performed with a polychromatic UV lamp (from 350 to 400 nm), with a power of 8 W (by Philips, Amsterdam, The Netherlands). Before any measurement, the samples were irradiated by the UV lamp for 50 min in order to remove the hydrocarbons from the sample surface [19]. The samples, 0.6 cm × 0.8 cm in size, were immersed in a solution (2 ml) containing MB or MO and de-ionized water (starting concentration 1.5×10^{-5} or 1×10^{-5} M, respectively). The mixture was irradiated by the UV lamp with an irradiance of 1.1 mW/cm². The irradiated solution was measured at regular time intervals with an UV-VIS spectrophotometer (PerkinElmer Lambda 35, PerkinElmer, Waltham, MA, USA) in a wavelength range from 500 to 800 nm for MB and from 350 to 650 nm for MO. The degradation of MB and MO was evaluated by the absorbance peak at 664 and 464 nm, respectively, in the Lambert-Beer regime [20]. The decomposition of the colorants in the absence of any catalyst materials was checked as a reference. Control experiments in the dark were conducted to clarify the contribution of the adsorption of the MB and MO at the sample surface.

Results and discussion

The scheme of the nanostructured Si template is reported in Figure 1a in cross view, where the Si is indicated in blue and Au in orange. Figure 1b shows a cross-view SEM image of the template, which is formed by pillars approximately 4 μm long.

The scheme of the nanostructured material after the deposition of the TiO₂ layer is shown in Figure 2a in cross view, where the TiO₂ is indicated in gray. A cross-view TEM image of the structure is shown in Figure 2b. The micrograph exhibits the Si substrate at the bottom of the structure; the Au nanoparticles involved in the



wet etching process are visible in dark contrast; the top of the Au nanoparticles and the Si structures resulted to be uniformly covered by the TiO₂ layer (10 nm thick). The analyses confirmed the excellent conformality of the deposition, thanks to the good diffusion of the precursors inside the nanostructured template, so the TiO₂ coverage came up to the bottom of the Si template, despite the high aspect ratio of the nanostructures (approximately 100). Figure 2c shows a schematic plan-view of the sample in order to give a visual idea of the template structure with nanocavities, while Figure 2d reports the relative TEM image. Here, the light area indicates the nanocavities of the porous structure, while the dark gray area indicates the Si covered by the titania layer. A 100% enhancement of the TiO₂ exposed surface area with respect to the flat film has been calculated by using the TEM data from several images similar to Figure 2d, thanks to the Gatan Digital Micrograph program. The diffraction pattern reported in Figure 2e unequivocally showed a polycrystalline anatase phase of the TiO₂, in good agreement with the literature [21]. X-ray diffraction analyses indicated an average grain size of approximately 15 nm. The polycrystalline structure of the titania films resulted to be the same for both the TiO₂/Si-template and the TiO₂ flat sample.

The photocatalytic activity of the synthesized materials was tested by the degradation of two dyes: MB, which is a dye of the thiazine family, and MO, which is a dye of the azo family (about the toxicity effects of these two dye families, the reader can refer to the 'Background' section). Figure 3 illustrates the discoloration measurements. In more detail, it reports the absorption spectra for the MB and MO (Figure 3a,b, respectively) solutions for different irradiation times for the TiO₂/Si-template samples. The absorbance peaks at 664 and 464 nm are a direct measurement of the MB and MO concentrations, respectively (through the Lambert-Beer law [20]), and thus, their decrease with the UV irradiation time is a measure of the photocatalytic decomposition of the MB and MO molecules. The absence of any new absorption bands is indicative of the absence of by-product formation during the dye degradation processes [22].

The residual concentrations ($\ln(C/C_0)$) of the MB and MO dyes are reported in Figure 4a,b, respectively (C is the concentration of the organic species, C_0 is the starting concentration of the organic species). Three samples were tested: the solution (MB or MO in de-ionized water) in the absence of any catalyst (squares), the solution with the TiO₂ flat film (circles), and the solution with the TiO₂/Si-template (triangles). The solution was first kept in the dark (from -240 min); at -180 min, the sample was immersed and kept in the dark (up to 0 min). The results reported in Figure 4a,b (gray-colored region) clearly show that there is a clear effect of the MB adsorption at the beaker walls in the absence of any




Figure 3 Absorption spectra for (a) MB and (b) MO solutions for different irradiation times for the TiO₂/Si-template samples.

catalyst materials (squares in Figure 4) in the first 30 min. This is not observed for the MO, probably due to the different nature of the two dyes: the MB is a cationic dye, while the MO is an anionic dye. The adsorption at the material surface in the dark is mainly negligible (circles and triangles in Figure 4), with the exception of a slight adsorption of the MB at the TiO₂/Si-template surface during the first 10 min (square at -180 min and triangle at -170 min). Thus, the efficiency of the nanostructured TiO₂ in degrading the dyes under the UV irradiation can be exclusively attributed to the photocatalytic effects. Figure 4 shows that the TiO₂/Si-template exhibits the greatest dye degradation. According to the Langmuir-Hinshelwood model, the photo-degradation reaction rate, k , of water contaminants is given by the following reaction:

$$\ln\left(\frac{C}{C_0}\right) = -kt, \quad (1)$$

where C is the concentration of the organic species, C_0 is the starting concentration of the organic species, and t




Figure 4 MB and MO degradation for the three samples. (a) MB and (b) MO degradation for the three samples: the solution (squares), the solution with the TiO_2 flat film (circles), and the solution with the TiO_2 /Si-template sample (triangles). Measurements in the dark are indicated with the gray-colored region, while the ones under the UV irradiation are indicated with the white-colored region. The linear fits of the experimental data are indicated with the continuous lines.

is the irradiation time [8]. By fitting the experimental data (lines in Figure 4) with Equation 1, the reaction rate for the MB degradation resulted to be $9.0 \times 10^{-4} \text{ min}^{-1}$ for the TiO_2 /Si-template, which is approximately three times higher than the reaction rate of the TiO_2 flat film ($3.6 \times 10^{-4} \text{ min}^{-1}$).

In order to evaluate whether the photocatalytic process might be limited by the diffusion process in water of the MB into the holes, we considered the diffusivity of MB in

water of approximately $10^{-8} \text{ cm}^2/\text{s}$ [23]. Assuming that this value can be applied also in our porous structure, it would give a diffusion time to reach the bottom of the nanostructured sample (few microns) of few seconds. Therefore, in the time scale of this experiment, the photocatalytic process is not diffusion limited. Furthermore, considering the slight adsorption of the MB at the TiO_2 /Si-template surface during the first 10 min (square at -180 min and triangle at -170 min), we directly

measured the adsorption rate (by Equation 1), which resulted to be $3.0 \times 10^{-3} \text{ min}^{-1}$, which is about three times higher than the reaction rate for the MB degradation, clearly demonstrating that the adsorption process is not limiting the photocatalytic one.

The reaction rate for the MO degradation resulted to be $4.7 \times 10^{-4} \text{ min}^{-1}$ for the TiO_2/Si -template, which is approximately 12 times higher than the reaction rate of the TiO_2 flat film ($4.0 \times 10^{-5} \text{ min}^{-1}$).

The synthesized material showed the highest degradation rate in the case of the MB. The observed difference between the MB and MO degradation efficiencies is not surprising, since it is well assessed that it is not possible to realize the *best* photocatalyst, but every TiO_2 material is able to efficiently degrade an organic compound, but less efficiently another one, due to the various parameters governing the photocatalytic reactions [24].

The marked difference in the photocatalytic response between the TiO_2 flat sample and the TiO_2/Si -template can be explained by taking into account the observed 100% enhancement of the TiO_2 exposed surface area with respect to the flat film. A quantitative comparison between the exposed surface area enhancement and the dye discoloration would not be a rigorous method because (1) the calculated enhancement is an underestimation, since with the used field of view of the microscopy images, there was a limit in the visibility of the holes with a diameter smaller than approximately 4 nm, and (2) the photocatalysis mechanism is complex.

The possible contribution of the Au nanoparticles in the photocatalytic activity of TiO_2 [25] can be excluded since the surface of gold is negligible with respect to the exposed surface of the TiO_2/Si -template (approximately 100 times less than the titania exposed surface). In addition, since the charge diffusion length in high-quality titania has been reported to be 3.2 nm for the anatase phase [13], and since the TiO_2 ALD layer reported in this work is 10 nm thick, we can exclude any contribution of the Au nanoparticles, placed underneath the TiO_2 layer. The same argument can be applied in order to exclude the possible effect of the Si support on the photocatalytic activity of the nanostructured TiO_2 .

Conclusions

In conclusion, we synthesized nanostructured TiO_2 with the main aim of enhancing the photocatalytic activity through an increase of the exposed surface area. The material was synthesized by using a nanostructured Si template obtained by metal-assisted wet etching of Si substrates. The realized template was covered with a thin layer of TiO_2 (10 nm thick), deposited by ALD. This approach avoided the use of nanoparticles and their consequent dispersion in water. The reported results show that the excellent conformality of the titania film on high-

aspect-ratio Si nanostructures is responsible for the improved efficiency in degrading dyes in water. In particular, the nanostructured TiO_2 exhibited a photo-degradation reaction rate for the MB and MO that is approximately 3 and approximately 12 times the rate of the TiO_2 flat film, respectively. Thus, our results demonstrate that the TiO_2 thin film coating of nanostructured surface can be efficiently used for water treatment reactors.

Competing interests

The authors declare that they have no competing interests.

Authors' contributions

VS performed the photo-degradation measurements and wrote the paper. GI supervised all the experiments, interpreted the data, and wrote the paper. LR conceived the study and performed the SEM analyses. MS and GN carried out and interpreted the TEM analyses. KB and BGS performed the ALD deposition. AI synthesized the nanostructured Si template. VP supervised the whole project. All authors read and approved the final manuscript.

Acknowledgements

We wish to thank R. Sanz for the XRD measurements and fruitful discussions. This research has been supported by the FP7 European Project WATER (Grant Agreement 316082). TEM analyses were performed at BeyondNano Sub-Angstrom lab, CNR-IMM, supported by the Italian Ministry of Education and Research with the project Beyond-Nano (PON a3_00363).

Author details

¹CNR-IMM Matis, Via S. Sofia 64, Catania 95123, Italy. ²Department of Physics and Astronomy, University of Catania, Via S. Sofia 64, Catania 95123, Italy.

³CNR-IMM, Z.I. VIII Strada 5, Catania 95121, Italy. ⁴Centre for Materials Science and Nanotechnology, Department of Physics, University of Oslo, Blindern, P.O. Box 1048, Oslo 0318, Norway. ⁵CNR-IPCF, Viale F. Stagno d'Alcontres 37, Faro Superiore, Messina 98158, Italy.

Received: 2 July 2014 Accepted: 4 August 2014

Published: 2 September 2014

References

1. Zollinger H: *Color Chemistry, Synthesis, Properties and Applications of Organic Dyes and Pigments*. 2nd edition. VCH: Weinheim; 1991.
2. Martínez-Huitle CA, Brillas E: Decontamination of wastewaters containing synthetic organic dyes by electrochemical methods: a general review. *Appl Catal B Environ* 2009, **87**:105–145.
3. Haveland-Smith RB, Combes RD: Genotoxicity of the food colours red 2G and brown FK in bacterial systems; use of structurally-related dyes and azo-reduction. *Food Chem Toxicol* 1980, **18**:223–228.
4. Vutskits L, Briner A, Klauser P, Gascon E, Dayer AG, Kiss JZ, Muller D, Licker MJ, Morel DR: Adverse effects of methylene blue on the central nervous system. *Anesthesiology* 2008, **108**:684–692.
5. Yahagi T, Degawa M, Seino Y, Matsushima T, Nagao M, Sugimura T, Hashimoto Y: Mutagenicity of carcinogenic azo dyes and their derivatives. *Cancer Lett* 1975, **19**:1–96.
6. Shannon MA, Bohn PW, Elimelech M, Georgiadis JG, Marinas BJ, Mayes AM: Science and technology for water purification in the coming decades. *Nature* 2008, **452**:301–310.
7. Malato S, Fernandez-Ibanez P, Maldonado MI, Blanco J, Gernjak W: Decontamination and disinfection of water by solar photocatalysis: recent overview and trends. *Catal Today* 2009, **147**:1–59.
8. Chong MN, Jin B, Chow CWK, Saint C: Recent developments in photocatalytic water treatment technology: a review. *Water Res* 2010, **44**:2997–3027.
9. Thompson TL, Yates JT Jr: Surface science studies of the photoactivation of TiO_2 - new photochemical processes. *Chem Rev* 2006, **106**:4428–4453.
10. Bendavid A, Martin PJ, Jamting A, Takikawa H: Structural and optical properties of titanium oxide thin films deposited by filtered arc deposition. *Thin Solid Films* 1999, **355**:6–11.
11. Serpone N, Sauvé G, Koch R, Tahiri H, Pichat P, Piccinini P, Pellizzetti E, Hidaka H: Standardization protocol of process efficiencies and activation

- parameters in heterogeneous photocatalysis: relative photonic efficiencies ζ_r . *J Photochem Photobiol A Chem* 1996, **94**:191–203.
- 12. Teoh WY, Scott JA, Amal R: Progress in heterogeneous photocatalysis: from classical radical chemistry to engineering nanomaterials and solar reactors. *J Phys Chem Lett* 2012, **3**:629–639.
 - 13. Luttrell T, Halpegamage S, Tao J, Kramer A, Sutter E, Batzill M: Why is anatase a better photocatalyst than rutile? - model studies on epitaxial TiO₂ films. *Sci Rep* 2014, **4**:4043.
 - 14. George SM: Atomic layer deposition: an overview. *Chem Rev* 2010, **110**:1111–131.
 - 15. Kemell M, Pore V, Tupala J, Ritala M, Leskela M: Atomic layer deposition of nanostructured TiO₂ photocatalysts via template approach. *Chem Mater* 2007, **19**:1816–1820.
 - 16. Hwang YJ, Boukai A, Yang P: High density n-Si/n-TiO₂ core/shell nanowire arrays with enhanced photoactivity. *Nano Lett* 2009, **9**:410–415.
 - 17. Irrera A, Artoni P, Iacona F, Pecora EF, Franzò G, Galli M, Fazio B, Boninelli S, Priolo F: Quantum confinement and electroluminescence in ultrathin silicon nanowires fabricated by a maskless etching technique. *Nanotechnology* 2012, **23**:075204.
 - 18. ISO: ISO:10678: *Fine Ceramics - Determination of Photocatalytic Activity of Surfaces in an Aqueous Solution Medium by Degradation of Methylene Blue*. Geneva: ISO; 2010.
 - 19. Wang R, Hashimoto K, Fujishima A, Chikuni M, Kojima E, Kitamura A, Shimohigoshi M, Watanabe T: Light-induced amphiphilic surfaces. *Nature* 1997, **388**:431–432.
 - 20. McNaught AD, Wilkinson A: *Compendium of Chemical Terminology*. 2nd edition. Oxford: Blackwell; 1997.
 - 21. Aarika J, Aidla A, Mandar H, Sammelselg V: Anomalous effect of temperature on atomic layer deposition of titanium dioxide. *J Crys Grow* 2000, **220**:531–537.
 - 22. Liu B, Wen L, Nakata K, Zhao X, Liu S, Ochiai T, Murakami T, Fujishima A: Polymeric adsorption of methylene blue in TiO₂ colloids - highly sensitive thermochromism and selective photocatalysis. *Chem Eur J* 2012, **18**:12705–12711.
 - 23. Fate G, Lynn DG: Molecular diffusion coefficients: experimental determination and demonstration. *J Chem Educ* 1990, **67**:536–538.
 - 24. Ryu J, Cho W: Substrate-specific photocatalytic activities of TiO₂ and multiactivity test for water treatment application. *Environ Sci Technol* 2008, **42**:294–300.
 - 25. Armelao L, Barreca D, Bottaro G, Gasparotto A, Maccato C, Maragno C, Tondello E, Stangar UL, Bergant M, Mahne D: Photocatalytic and antibacterial activity of TiO₂ and Au/TiO₂ nanosystems. *Nanotechnology* 2007, **18**:375709.

doi:10.1186/1556-276X-9-458

Cite this article as: Scuderi et al.: TiO₂-coated nanostructures for dye photo-degradation in water. *Nanoscale Research Letters* 2014 9:458.

Submit your manuscript to a SpringerOpen® journal and benefit from:

- Convenient online submission
- Rigorous peer review
- Immediate publication on acceptance
- Open access: articles freely available online
- High visibility within the field
- Retaining the copyright to your article

Submit your next manuscript at ► springeropen.com