

SCIENTIFIC REPORTS

OPEN

Author Correction: Electrochemical Performance of Supercapacitor with Stacked Copper Foils Coated with Graphene Nanoplatelets

S. L. Chiam¹, H. N. Lim^{1,2}, S. M. Hafiz², A. Pandikumar³ & N. M. Huang⁴

Correction to: *Scientific Reports* <https://doi.org/10.1038/s41598-018-21572-x>, published online 15 February 2018

This Article contains a typographical error in the Results and Discussion section where,

“This value is 213 times higher compared to graphitic powder ($2.78 \text{ m}^2/\text{g}$)⁶, indicating that graphite was significantly exfoliated into few graphitic layers ($2630/591 \approx 4$) by thermal exfoliation.”

should read:

“This value is 213 times higher compared to graphitic powder ($2.78 \text{ m}^2/\text{g}$)⁶, indicating that graphite was significantly exfoliated into few graphitic layers ($2630/591 \approx 4$) by thermal exfoliation.”

In addition, this Article contains an error in the order of the Figures. Figures 2 and 3 were published as Figures 3 and 2 respectively. The correct Figures 2 and 3 appear below as Figures 1 and 2 respectively.

¹Department of Chemistry, Faculty of Science, Universiti Putra Malaysia, 43400 UPM, Serdang, Selangor, Malaysia.

²Materials Synthesis and Characterization Laboratory, Institute of Advanced Technology, Universiti Putra Malaysia, 43400 UPM, Serdang, Selangor, Malaysia. ³Electrochemical Materials Science and Functional Materials Division, CSIR-Central Electrochemical Research Institute, Karaikudi, 630003, India. ⁴New Energy Science & Engineering Programme, University of Xiamen Malaysia, Jalan SunSuria, Bandar SunSuria, 43900, Sepang, Selangor Darul Ehsan, Malaysia. Correspondence and requests for materials should be addressed to H.N.L. (email: janetlimhn@gmail.com) or S.M.H. (email: syedahfiz27@gmail.com) or N.M.H. (email: huangnayming@xmu.edu.my)




Figure 1. Nitrogen adsorption and desorption isotherms for GNPs.




Figure 2. Electrochemical performance of stacked device against single device: (a) CV profiles at 100 mV s^{-1} , (b) GCD profiles at 3 A g^{-1} , (c) Nyquist plot with inset showing magnified version at low-frequency region, and (d) performance durability test at 3 A g^{-1} .



Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

© The Author(s) 2018