

# Multi-reference global registration of individual A-lines in adaptive optics optical coherence tomography retinal images (Publisher's Note)

Kazuhiro Kurokawa,<sup>a</sup> James A. Crowell,<sup>a</sup> Nhan Do,<sup>b,c</sup>  
John J. Lee,<sup>b</sup> and Donald T. Miller<sup>a</sup>

<sup>a</sup>Indiana University, School of Optometry, Bloomington, Indiana, United States

<sup>b</sup>Indiana University–Purdue University, Purdue School of Engineering and Technology,  
Indianapolis, Indiana, United States

<sup>c</sup>Google, Mountain View, California, United States

[DOI: [10.1117/1.JBO.26.1.019803](https://doi.org/10.1117/1.JBO.26.1.019803)]

This article [*J. Biomed. Opt.* **26**(1), 016001 (2021) doi: [10.1117/1.JBO.26.1.016001](https://doi.org/10.1117/1.JBO.26.1.016001)] was originally published on 6 January 2021 with an error in Eq. (14). Due to editorial oversight, two blank spaces appeared where two variables should have appeared.

Original error:

$$f(R, R') = \left\| \sum_{R'=1}^N \sum_{R=1}^N \sum_{i \in W_{R,R'}} (\vec{p}_{i,T,R} - \vec{p}_{i,T,R'} + \vec{\tau}_R - \vec{\tau}_{R'})^2 \right\|. \quad (14)$$

Corrected:

$$f(R, R') = \left\| \sum_{R'=1}^N \sum_{R=1}^N \sum_{i \in W_{R,R'}} (\vec{p}_{i,T,R} - \vec{p}_{i,T,R'} + \vec{\tau}_R - \vec{\tau}_{R'})^2 \right\|. \quad (14)$$

The error was corrected on 8 January 2021.