ONLINE DATA SUPPLEMENT

Six-Minute Walking Versus Shuttle Walking: Responsiveness to Bronchodilation in Chronic Obstructive Pulmonary Disease

Authors:

Véronique Pepin, Julie Brodeur, François Whittom, Yves Lacasse, Julie Milot,

Pierre LeBlanc, François Maltais.

METHODS

Study design

A schematic representation of the study protocol is presented in Figure E1.

Incremental Shuttle Walk

The incremental shuttle walk was performed in an enclosed corridor on a flat 10-meter-long course. As previously described by Singh and colleagues¹, patients walked around two cones, each positioned 0.5 m from either end, following the rhythm dictated by the audio signal. Walking speed was initially set at 0.50 meters/second and subsequently increased by 0.17 meter/second every minute until the patient reached a symptom-limited maximum.

Endurance Shuttle Walk

The endurance shuttle walk was performed in an enclosed corridor on a flat 10 meter-long course, as previously described by Revill and colleagues². After a two minute warm up, walking speed was set at the speed corresponding to 80% of \P_2 peak, as predicted from the incremental shuttle walk. Before each test, patients were instructed to walk for as long as possible at the speed dictated by the auditory signal. Patients were notified that no further

1

encouragement would be provided to them during the test. This was done to avoid any potential confounding effect on their performance³.

Six-Minute Walking Test

The 6MWT was completed in an enclosed corridor on a flat 30-meter-long course according to the procedures recommended by the American Thoracic Society (ATS)⁴. Before each test, patients were instructed to cover as much ground as possible in the allotted time period. Patients were also notified that no encouragement would be provided to them during the test, but that they would be kept aware of time, as per ATS guidelines⁴. Test time was recorded for every 60 meters completed to estimate walking speed.

Physiological Measures

Cardiorespiratory Parameters

Quadriceps force measurements

Before and after each endurance test, quadriceps twitch force was evaluated during a single magnetic stimulation of the femoral nerve as previously described by our group⁷(Figure E2). From a supine position, the dominant leg was stabilised on a wooden frame with the knee

and the hip flexed at 45°. The box design ensured that the leg position was standardised during all measurements and that the length of the quadriceps remained identical throughout the experimentation. The ankle was attached to a strain gauge (Hewlett-Packard, Palo Alto, Ca) through a non-elastic ankle strap to measure the isometric knee extension tension. Care was taken to ensure that the ankle strap and transducer were perpendicular to the leg and the frame box. The position of the strap was marked on the leg ensuring that it remained identical throughout the pre and post exercise measurements. The strain gauge signal was amplified (Hewlett-Packard amplificaters 8811A, Hewlett-Packard, Palo Alto, Ca), transformed by an analog transducer (Biopac system, Santa Barbara, CA) and stored on a computer for data analysis (Acknowledge software, Biopac, Santa Barbara, CA).

The femoral nerve was stimulated using a commercial magnetic stimulator (Magstim 200; Magstim Co Ltd; Whitland, Dyfed, Wales, UK) and a figure-of-eight coil. The coil was positioned over the femoral nerve just lateral to the femoral artery. The coil position leading to the strongest muscle contraction was localized and used in subsequent twitches. Since potentiated twitches appear to be more sensitive for detecting fatigue than non potentiated twitches⁸, each quadriceps twitch force was obtained 1 second after a 5-second isometric contraction. A set of 10 potentiated twitches was performed before (after 15 minutes of rest), 10, 20 and 30 minutes after exercise. All potentiated twitches were obtained at 100% of stimulator output. Reported twitch force of quadriceps values are the mean of the three strongest contractions. The preload on the gauge was subtracted from the peak tension measured during the twitch maneuvers so that the reported twitch force values include only the tension developed by the quadriceps contraction.

REFERENCES

- E1. Singh SJ, Morgan MD, Scott S, Walters D, Hardman AE. Development of a shuttle walking test of disability in patients with chronic airways obstruction. *Thorax* 1992;47:1019-1024.
- E2. Revill SM, Morgan MD, Singh SJ, Williams J, Hardman AE. The endurance shuttle walk: a new field test for the assessment of endurance capacity in chronic obstructive pulmonary disease. *Thorax* 1999;**54**:213-222.
- E3. Guyatt GH, Pugsley S, Sullivan MJ, et al. Effect of encouragement on walking test performance. *Thorax* 1984;**39**:818-822.
- E4. ATS statement: guidelines for the six-minute walk test. Am J Respir Crit Care Med 2002;**166**:111-117.
- E5. McLaughlin JE, King GA, Howley ET, Bassett DR, Jr., Ainsworth BE. Validation of the COSMED K4 b2 portable metabolic system. *Int J Sports Med* 2001;**22**:280-284.
- E6. Palange P, Forte S, Onorati P, Manfredi F, Serra P, Carlone S. Ventilatory and metabolic adaptations to walking and cycling in patients with COPD. *J Appl Physiol* 2000;**88**:1715-1720.
- E7. Saey D, Debigaré R, LeBlanc P, et al.. Contractile leg fatigue after cycle exercise: a factor limiting exercise in patients with COPD. *Am J Respir Crit Care Med* 2003;**168**:425-430.
- E8. Kufel TJ, Pineda LA, Mador MJ. Comparison of potentiated and unpotentiated twitches as an index of muscle fatigue. *Muscle Nerve* 2002;**25**:438-444.

LEGEND FOR FIGURES

Figure E1. Schematic representation of the study protocol. PFT: pulmonary function test; 6MWT: six-minute walking test; ESW: endurance shuttle walk; PL: placebo; IB: ipratropium bromide.

Figure E2. Schematic representation of the experimental setup showing the strain gauge (A), the non elastic ankle strap (B), the figure-of-eight coil (C) and the wooden frame (D) ensuring that the leg positioning during the magnetic stimulation was identical throughout the measurements.




Figure E1.




Figure E2.