

**Table S1 Mutant genotypes**

Name	Description
<i>w</i> <sup>1118</sup>	<i>white</i> <sup>-</sup>
WT	attP2[S2E <sup>wt</sup> EVE <sup>YFP</sup> ] 16.4kb <i>eve</i> locus with wild type stripe 2 enhancer (S2E) and a YFP tag at the C-terminus of the <i>eve</i> coding region, integrated on the third chromosome
MSE	attP2[S2E <sup>MSE</sup> EVE <sup>YFP</sup> ] 16.4kb <i>eve</i> locus with 244bp deleted from S2E (Fig. 2A) and a YFP tag at the C-terminus of the <i>eve</i> coding region, integrated on the third chromosome
<i>eve</i> <sup>R13</sup>	Null allele carrying a coding point mutation
<i>gt</i> <sup>X11</sup>	Null allele
<i>gt</i> <sup>YFP</sup>	attP2[GT <sup>YFP</sup> ] 26.2kb region of the <i>gt</i> locus with a YFP tag at the C-terminus of the <i>gt</i> coding region, integrated on the third chromosome
<i>eve</i> <sup>ΔMSE</sup>	Native locus in which the MSE region of the stripe 2 enhancer is deleted and replaced with <i>w</i> <sup>+</sup> sequence (Ludwig <i>et al.</i> , 2005)