

Supplementary Table 2. Diagnostic value of SWE values, including mean stiffness, node size, max stiffness, and ratio

Characteristic	Cutoff point	TP	TN	FP	FN	SN (95% CI)	SP (95% CI)	Accuracy (95% CI)	PPV (95% CI)	NPV (95% CI)
Mean stiffness (kPa)	>30.6	24	170	17	17	58.5 (43.5–73.6)	90.9 (86.8–95.0)	85.1 (80.5–89.7)	58.5 (43.5–73.6)	89.3 (84.3–94.2)
Node size (mm)	>8.9	25	133	54	16	60.1 (46.0–75.9)	71.1 (64.6–77.6)	69.3 (63.3–75.3)	31.7 (21.4–41.9)	89.3 (84.3–94.2)
Max stiffness (kPa)	>38.6	24	168	19	17	58.5 (43.5–73.6)	89.8 (85.5–94.2)	84.2 (79.5–88.9)	55.8 (41.0–70.7)	90.8 (86.6–95.0)
Ratio	>2.37	29	166	21	12	70.7 (56.8–84.7)	88.8 (84.2–93.3)	85.5 (81.0–90.1)	58.0 (44.3–71.7)	93.3 (89.6–96.9)

SWE=shear-wave elastography; TP=true positives; TN=true negatives; FP=false positives; FN=false negatives; SN=sensitivity; CI=confidence interval; SP=specificity; PPV=positive predictive value; NPV=negative predictive value.