

Supporting Information (SI)

Synthesis and properties of tung oil-based unsaturated co-ester resins bearing steric hindrance

Chengguo Liu^{a,*}, Qiong Wu^{a,b}, Rongrong An^c, Qianqian Shang^a, Guodong Feng^a, Yun Hu^a, Puyou Jia^a, Yonghong Zhou^{a,*}, Wen Lei^{b,*}

^a Institute of Chemical Industry of Forest Products, Chinese Academy of Forestry; National Engineering Lab for Biomass Chemical Utilization; Key Lab on Forest Chemical Engineering, State Forestry Administration; Key Lab of Biomass Energy and Material, Jiangsu Province; Nanjing 210042, P. R. China

^b College of Science, Nanjing Forestry University, Nanjing 210037, P. R. China

^c College of Geographic and Biologic Information, Nanjing University of Posts and Telecommunications, Nanjing 210023, P. R. China

* Correspondence: **Corresponding authors:** Chengguo Liu. E-mail: liuchengguo@icifp.cn; Tel.: +86-25-85482520; Fax: +86-25-85482520; Yonghong Zhou. E-mail: zyh@icifp.cn; Tel.: +86-25-854825777; Fax: +86-25-854825777; Wen Lei. E-mail: njfuleiwen@163.com; Tel.: +86-25-85427206; Fax: +86-25-85427206.



Fig. S1 PTFE mold used for preparing samples of DMA test
(Shape: Cuboid; Size: 80×10×4 mm³)



Fig. S2 PTFE mold used for preparing samples of tensile property test
(Shape: Dumbbell; Length overall: 63.5 mm; Width overall: 9.53 mm; Size of the
narrow middle part: $9.53 \times 3.18 \times 3.2 \text{ mm}^3$)